



**STAY  CONNECTED**

## IAB44 C

<p><b>PROCESSOR</b> MediaTek MT7628 128MB DDR RAM, 32MB Flash</p>	<p><b>CELLULAR</b> Dual SIM 4G/3G/2G, External 5dB antennas</p>	<p><b>Wi-Fi</b> 2.4GHz, 300Mbps AP/Station, External 5dB antennas</p>
<p><b>ETHERNET</b> 1x LAN 10/100 1x WAN 10/100</p>	<p><b>POWER</b> 9-30V DC Input</p>	<p><b>OPERATING SYSTEM</b> Open-WRT Linux</p>
<p><b>NMS</b> Easy remote management and monitoring for large-scale deployment.</p>		



## HARDWARE SPECIFICATION

CPU	MediaTek MT7628
FLASH	32MB
RAM	128MB
WAN	1x 10/100
LAN	1x 10/100
Serial Interface	1xRS232, 1x RS485
GPIO	4xDI/O, 2xAI (1xAnalog current, 1xAnalog voltage)
USB interface	1xUSB-H
SIM	2x Nano SIM
Reset	Pinhole Reset Button
Wi-Fi	802.11b/g/n
Antenna	Cellular: 2x SMA Connector, Wi-Fi: 2x SMA connector
Enclosure	Industrial Aluminium alloy Enclosure
Mounting	Din-rail mount (As an optional accessory)
Design	Fan less
Dimensions	112 x 35 x 92mm (W x H x D)
Weight	400 gm
Status LED	Single strength (RSSI), PWR, SIM1 & SIM2 LED, DI/O Status LED, Rx & Tx LED
Input Power	9-30 Vdc
<b>Operational &amp; Environmental</b>	
Storage Temperature	-30 ~ 75°C
Operating Temperature	-25 ~ 65°C
Humidity	10 ~ 90% (non-condensing)
Ingress Protection Rating	IP30



## SOFTWARE FEATURES

### Cellular

Cellular Module	4G (LTE) - Cat 4 up to 150 Mbps, 3G – up to 42 Mbps, 2G – up to 236.8 Kbps
Status	Single strength (RSSI), SINR, RSRP, RSRQ
Band Management	Auto/User configurable & Operator Lock
APN	Configurable, Auto APN (Planned)
Modem configuration mode	Single SIM, Dual SIM
SIM switching	Signal strength, ICMP echo, Data limit based
Bridge	Direct connection (bridge) between mobile ISP and device on LAN (Planned)
PDP Type	IPv4, IPv6, Dual stack
Passthrough	Router assigns its mobile WAN IP address to another device on LAN (Planned)

### Wi-Fi

Wi-Fi Mode	Access Point, Station, Guest Wi-Fi, Repeater
Encryption	TKIP, AES
Technology	802.11 b/g/n with 20 MHz
Authentication	WPA (PSK), WPA2 (PSK)
TX Power	Configurable
Wi-Fi Scheduler	Scheduled ON/OFF

### Firewall & Networking

Routing	Static routing
Network Protocols	TCP, UDP, IPv4, IPv6, ICMP, NTP, DNS, HTTP, HTTPS, FTP, PPP, SSH, DHCP, SNMP (Planned), TR069 (Planned)
Connecting Monitoring	Ping Reboot, Scheduled Periodic Reboot
Firewall features	Port forward, traffic rules, SNAT, Zone- Zone traffic control
DHCP	Static and Dynamic



Failover	Configurable Failover option for Cellular WAN, Wired, and Wi-Fi WAN
Authentication	Pre-shared key, X.509 certificates
VLAN	Port-based VLAN, Tag-based VLAN 802.1ad
Other	MAC binding, black/whitelisting
VPN	Open VPN, IPsec, GRE, L2TP, PPTP, GRE over IPsec
Open VPN	TUN/TAP (Planned)
IPsec	IKEv1, IKEv2, Encryption: DES, 3DES, AES128, AES192, AES256
PPTP, L2TP	WAN with PPTP/L2TP configuration for secure broadband connection
<b>Gateway</b>	
Gateway Protocols	Modbus RTU, Modbus TCP
Data sender	HTTP, MQTT, Azure MQTT
<b>Operating System</b>	
Operating System	Open-WRT based Linux OS
Supported Languages	Shell scripting, C, C++
Development tools	SDK package with built environment provided (Optional)
<b>Standard Packaging</b>	Product, 2x Cellular Rubber Duck Antennas, 2x Wi-Fi Rubber Duck Antennas, RS485 TB, DI/O TB, AI TB, 24Vdc Output TB, 0.5-meter Power Cord, 01-meter Ethernet cable.

\*All rights reserved, subject to change without prior notice.

