



STAY  CONNECTED

RF44 M

<p>PROCESSOR MediaTek MT7628 64MB DDR RAM, 32MB Flash</p>	<p>CELLULAR 4G/3G/2G with Single SIM, External 5dbi antenna</p>	<p>Wi-Fi 2.4GHz, 300Mbps AP. External 5dBi antenna.</p>
<p>ETHERNET 1x LAN 10/100</p>	<p>POWER 5V DC Input</p>	<p>OPERATING SYSTEM Open-WRT Linux</p>
<p>NMS Easy remote management and monitoring for large scale deployment.</p>		



HARDWARE SPECIFICATION

CPU	MediaTek MT7628
FLASH	32MB
RAM	64MB
LAN	1x 10/100
SIM	1x Nano SIM
Reset	Pinhole Reset Button
Wi-Fi	802.11b/g/n
Antenna	Cellular: 2x SMA Connector, Wi-Fi: 2x SMA connector
Enclosure	Metal Enclosure
Mounting	Din-rail mount (As an optional accessory)
Design	Fanless
Dimensions	90 x 27 x 80mm (W x H x D)
Weight	240 gm
Status LED	Mode, Connectivity, Wi-Fi, Power
Input Power	5 Vdc

Operational & Environmental

Storage Temperature	-30 ~ 70°C
Operating Temperature	-20 ~ 60°C
Humidity	10 ~ 90% (non-condensing)
Ingress Protection Rating	IP30

SOFTWARE FEATURES

Cellular

Cellular Module	4G (LTE) - Cat 4 up to 150 Mbps, 3G - up to 42 Mbps, 2G - up to 236.8 Kbps
Status	Single strength (RSSI), SINR, RSRP, RSRQ



Band Management	Auto/User configurable & Operator Lock
APN	Configurable, Auto APN (Planned)
Modem configuration mode	Single SIM
SIM switching	Signal strength, ICMP echo, Data limit based
PDP Type	IPv4, IPv6, Dual stack
Wi-Fi	
Wi-Fi Mode	Access Point, Guest Wi-Fi
Encryption	TKIP, AES
Technology	802.11 b/g/n with 20 MHz, 40 MHz
Authentication	WPA (PSK), WPA2 (PSK)
TX Power	Configurable
Wi-Fi Scheduler	Scheduled ON/OFF
Firewall & Networking	
Routing	Static routing
Network Protocols	TCP, UDP, IPv4, IPv6, ICMP, NTP, DNS, HTTP, HTTPS, FTP, PPP, SSH, DHCP, SNMP (Planned), TR069 (Planned)
Connecting Monitoring	Ping Reboot, Scheduled Periodic Reboot
Firewall features	Port forward, traffic rules, SNAT, Zone- Zone traffic control
DHCP	Static and Dynamic
Failover	Configurable Failover option for Cellular WAN, Wi-Fi WAN
Authentication	Pre-shared key, X.509 certificates
Other	MAC binding, black/whitelisting
VPN	Open VPN, IPsec, GRE, L2TP, PPTP, GRE over IPsec
Open VPN	TUN/TAP (Planned)
IPsec	IKEv1, IKEv2, supports up to 4xVPN IPsec client. Encryption: DES, 3DES, AES128, AES192, AES256



PPTP, L2TP	WAN with PPTP/L2TP configuration for secure broadband connection
Remote Management	
NMS	Remote monitoring of SILBO Networking products
NMS VPN	Remote access of SILBO and non SILBO Networking products using NMS VPN
Operating System	
Operating System	Open-WRT based Linux OS
Supported Languages	Shell scripting, C, C++
Development tools	SDK package with built environment provided (Optional)
Standard Packaging	Product, 2x Cellular Rubber Duck Antennas, 2x Wi-Fi Rubber Duck Antennas, 0.5 meter Ethernet cable, 0.5 meter Power cable.

*All rights reserved, subject to change without prior notice.

