



STAY  CONNECTED

RK04 Dual

PROCESSOR MediaTek MT7621 256MB DDR RAM, 32MB Flash	CELLULAR Dual Module Dual SIM 4G/3G/2G, External 5dB antennas	
ETHERNET 1x WAN 10/100/1000 4x LAN 10/100/1000	POWER 12V DC Input	OPERATING SYSTEM Open-WRT Linux
NMS Easy remote management and monitoring for large-scale deployment.		



HARDWARE SPECIFICATION

CPU	MediaTek MT7621
FLASH	32MB
RAM	512MB
WAN	1x 10/100/1000
LAN	4x 10/100/1000
SIM	Dual 4G Modem, Dual SIM
Reset	Pinhole Reset Button
Antenna	Cellular: 4x SMA Connector
Enclosure	Metal Enclosure
Mounting	Din-rail mount (As an optional accessory)
Design	Fanless
Dimensions	209 x 30 x 154 mm (W x H x D)
Weight	950 gm
Power Supply	Optional PSU (12 Vdc)
Input Power	12 Vdc

Operational & Environmental

Storage Temperature	-30 ~ 70°C
Operating Temperature	-20 ~ 60°C
Humidity	10 ~ 90% (non-condensing)
Ingress Protection Rating	IP30

SOFTWARE FEATURES

Cellular

Cellular Module	4G (LTE) - Cat 4 up to 150 Mbps, 3G - up to 42 Mbps, 2G - up to 236.8 Kbps
-----------------	--



Status	Single strength (RSSI), SINR, RSRP, RSRQ, SIM Status
Band Management	Auto/User configurable & Operator Lock
APN	Configurable, Auto APN (Planned)
Modem configuration mode	Single Cellular Single SIM, Dual cellular Dual SIM
SIM switching	Signal strength, ICMP echo, Data limit based
Bridge	Direct connection (bridge) between mobile ISP and device on LAN (Planned)
PDP Type	IPv4, IPv6, Dual stack
Passthrough	Router assigns its mobile WAN IP address to another device on LAN (Planned)
Firewall & Networking	
Routing	Static routing, Dynamic Routing (Planned)
Network Protocols	TCP, UDP, IPv4, IPv6, ICMP, NTP, DNS, HTTP, HTTPS, FTP, PPP, SSH, DHCP, SNMP (Planned), TR069 (Planned)
Connecting Monitoring	Ping Reboot, Scheduled Periodic Reboot
Firewall features	Port forward, traffic rules, SNAT, Zone- Zone traffic control
DHCP	Static and Dynamic
Failover	Configurable Failover option for Cellular and wired WAN.
Authentication	Pre-shared key, X.509 certificates
VLAN	Port-based VLAN, Tag-based VLAN 802.1ad
Other	MAC binding, black/whitelisting
VPN	Open VPN, IPsec, GRE, L2TP, PPTP, GRE over IPsec
Open VPN	TUN/TAP (Planned)
IPsec	IKEv1, IKEv2, supports up to 4xVPN IPsec client. Encryption: DES, 3DES, AES128, AES192, AES256
PPTP, L2TP	WAN with PPTP/L2TP configuration for secure broadband connection (Planned)
Remote Management	
NMS	Remote monitoring of SILBO Networking products



NMS VPN	Remote access of SILBO and non SILBO Networking products using NMS VPN
Operating System	
Operating System	Open-WRT based Linux OS
Supported Languages	Shell scripting, C, C++, Python (Optional)
Development tools	SDK package with built environment provided (Optional)
Standard Packaging	Product Up to 4 Cellular Rubber Duck Antennas Power cable 0.5-meter Ethernet cable

*All rights reserved, subject to change without prior notice.

