



STAY  CONNECTED

RM60 M

<p>PROCESSOR MediaTek MT7621 256MB DDR RAM, 32MB Flash</p>	<p>Wi-Fi b/g/n/ac/ax, AP, Station, Mesh, Internal 5dB antennas</p>	
<p>ETHERNET 1x WAN 10/100/1000 3x LAN 10/100/1000</p>	<p>POWER 12V DC Input</p>	<p>OPERATING SYSTEM Open-WRT Linux</p>
<p>NMS Easy remote management and monitoring for large scale deployment.</p>		



HARDWARE SPECIFICATION

CPU	MediaTek MT7621
FLASH	32MB
RAM	256MB
WAN	1x 10/100/1000
LAN	3x 10/100/1000
Wi-Fi	802.11b/g/n/ac/ax
Antennas	2x 5G Wi-Fi antenna, 2x2.4Ghz Wi-Fi Antennas
Reset	Pinhole Reset Button
Enclosure	Metal Enclosure
Mounting	Din-rail mount (As an optional accessory)
Design	Fan less
Dimensions	100 x 38 X 110 mm (W x H x D)
Weight	330 gm
Status LED	Mode, Connectivity, Wi-Fi, Power
Input Power	12 Vdc

Operational & Environmental

Storage Temperature	-30 ~ 60°C
Operating Temperature	-20 ~ 50°C
Humidity	10 ~ 90% (non-condensing)
Ingress Protection Rating	IP30

SOFTWARE FEATURES

Wi-Fi	
Wi-Fi Mode	Access Point, Station, Guest Wi-Fi, Repeater, Wi-Fi Mesh
Encryption	TKIP, AES



Technology	802.11 b/g/n/ac/ax with 20 MHz, 40 MHz, 80 MHz
Authentication	WPA (PSK), WPA2 (PSK)
Firewall & Networking	
Routing	Static routing
Network Protocols	TCP, UDP, IPv4, ICMP, NTP, DNS, HTTP, HTTPS, PPP, SSH, DHCP
Firewall features	Port forward, traffic rules, SNAT
DHCP	Static and Dynamic
Failover	Configurable Failover option for Cellular WAN, Wired WAN
VPN	L2TP, PPTP
Standard Packaging	Product 4x Rubber Duck Wi-Fi Antennas Power Adaptor (optional Accessory) 0.5-meter Ethernet cable

*All rights reserved, subject to change without prior notice.

