



**STAY  CONNECTED**

## XA-82-2

<p><b>ETHERNET</b> 8x 10/100/1000</p>	<p><b>PoE Budget</b> 240 W</p>	<p><b>POWER</b> 9-43 VDC: No PoE Out 44-57 VDC: PoE Out</p>
---	------------------------------------	---



<b>HARDWARE SPECIFICATION</b>	
<b>LAN</b>	8 x 10/100/1000 Mbps (MDI/MDIX)
<b>SFP</b>	2 x SFP
<b>PoE</b>	LAN Port 1 – 8 (PoE Out)
<b>PoE Standard</b>	802.3at & 802.3af
<b>PoE Budget (Per Port)</b>	30 W (Max)
<b>Total PoE Budget</b>	240 W(Max)
<b>MAC Address table entries</b>	2000
<b>Jumbo Frame</b>	9216 bytes
<b>Buffer size</b>	128 KB
<b>Power</b>	
<b>Socket type</b>	2 Pin TB
<b>Input Voltage</b>	9-57 Vdc (PoE out will work from 44-57Vdc Input)
<b>Power Consumption</b>	5.5 W (Non PoE) / 245.5 W (With PoE)
<b>Operating Temperature</b>	-30 ~ 65°C
<b>Humidity</b>	10 ~ 90% (non-condensing)
<b>Ingress Protection Rating</b>	IP30
<b>Mechanical</b>	
<b>Housing</b>	Industrial Aluminium
<b>Dimension</b>	58x112x114mm (HHxWWxDD)
<b>Weight</b>	300 Gm*
<b>LED Status</b>	PWR(On/Off), LAN Activity LED (Green: Active connection, Orange: 1000 Mbps), SFP Status LED (Green: Connection status)
<b>Standard Packaging</b>	Product

\*All rights reserved, subject to change without prior notice.

