



STAY  CONNECTED

RG44

<p>PROCESSOR MediaTek MT7621, 512MB DDR RAM, 32MB Flash</p>	<p>CELLULAR 4G/3G/2G with Dual cellular, Dual SIM, External antennas Of 5dBi</p>	<p>Wi-Fi 2.4GHz, 300Mbps AP/Station, External 5dBi antenna.</p>
<p>ETHERNET 1x 10/100/1000 4x 10/100/1000</p>	<p>POWER 12V DC Input</p>	<p>OPERATING SYSTEM Open-WRT Linux</p>
<p>NMS Easy remote management and monitoring for large-scale deployment.</p>		



HARDWARE SPECIFICATION

CPU	MediaTek MT7621
FLASH	32MB
RAM	512MB
WAN	1x 10/100/1000
LAN	4x 10/100/1000
SIM	2x Nano SIM
Reset	Pinhole Reset Button
Wi-Fi	802.11b/g/n
Antenna	Cellular: 2x SMA Connector, Wi-Fi: 2x SMA connector
Enclosure	Metal Enclosure
Mounting	Din-rail mount (As an optional accessory)
Design	Fanless
Dimensions	165 x 30 x 110mm (W x H x D)
Weight	600 gm
Status LED	Mode, Connectivity, SIM1, SIM2, Power
Input Power	12 Vdc

Operational & Environmental

Storage Temperature	-25 ~ 65°C
Operating Temperature	-20 ~ 60°C
Humidity	10 ~ 90% (non-condensing)
Ingress Protection Rating	IP30

SOFTWARE FEATURES

Cellular

Cellular Module	4G (LTE) - Cat 4 up to 150 Mbps, 3G - up to 42 Mbps, 2G - up to 236.8 Kbps
Status	Single strength (RSSI), SINR, RSRP, RSRQ



Band Management	Auto/User configurable & Operator Lock
APN	Configurable, Auto APN (Planned)
Modem configuration mode	Single Cellular Single SIM, Dual Cellular Dual SIM
SIM switching	Signal strength, ICMP echo, Data limit based
Bridge	Direct connection (bridge) between mobile ISP and device on LAN (Planned)
PDP Type	IPv4, IPv6, Dual stack
Passthrough	The router assigns its mobile WAN IP address to another device on LAN (Planned)
Wi-Fi	
Wi-Fi Mode	Access Point
Encryption	TKIP, AES
Technology	802.11 b/g/n with 20 MHz, 40 MHz
Authentication	WPA (PSK), WPA2 (PSK)
TX Power	Configurable
Wi-Fi Scheduler	Scheduled ON/OFF
Firewall & Networking	
Routing	Static routing
Network Protocols	TCP, UDP, IPv4, IPv6, ICMP, NTP, DNS, HTTP, HTTPS, PPP, SSH, DHCP
Connecting Monitoring	Ping Reboot, Scheduled Periodic Reboot
Firewall features	Port forward, traffic rules, SNAT, Zone- Zone traffic control
DHCP	Static and Dynamic
Failover	Configurable Failover option for Cellular WAN, Wired, and Wi-Fi WAN
Authentication	Pre-shared key, X.509 certificates
VLAN	Port-based VLAN, Tag-based VLAN 802.1ad (Planned)
Other	MAC binding, black/whitelisting



VPN	Open VPN, IPsec, GRE, L2TP, PPTP, GRE over IPsec
Open VPN	TUN/TAP (Planned)
IPsec	IKEv1, IKEv2, supports up to 4xVPN IPsec clients. Encryption: DES, 3DES, AES128, AES192, AES256
PPTP, L2TP	WAN with PPTP/L2TP configuration for secure broadband connection
Remote Management	
NMS	Remote monitoring of SILBO Networking products
NMS VPN	Remote access of SILBO and non-SILBO Networking products using NMS VPN
Operating System	
Operating System	Open-WRT based Linux OS
Supported Languages	Shell scripting, C, C++, Python (Optional)
Development tools	SDK package with built environment provided (Optional)
Standard Packaging	Product 4x Cellular Rubber Duck Antennas 2x Wi-Fi Rubber Duck Antennas Power cable 0.5 mts Ethernet cable

*All rights reserved, subject to change without prior notice.

